
Måleinstrumenter: ▸ Testo 330-2LL

LL = LONGLIFE



LongLife celler:
Instrumentet er levert med celler for lang levetid. O2 og CO cellene kan leve opp til 6år og Testo garanterer 4års levetid.

BRUKERVENLIG



Lett og bruke og vedlikeholde:
Testo sine instrumenter er meget lett og bruke og holde vedlike. Hurtigkoblinger på slangesett og moderne design.

Takke være de nye LL-cellene (LongLife) er Testo 330-2LL et instrument med lang levetid på celler og gir raske måleresultater.

Instrumentet er meget brukervenlig og kan lett kobles til en printer eller mot en PC via USB-kabel. Instrumentet veier kun 600g og har et moderne design.

Måleområder er temperatur, forbrenningsvirkningsgrad, røykgasstap, O2, CO2 og trekk. Den kan også bygges ut så den måler NO og NOlow.

Ved å kombinere instrumentet med en trådløs printer kan man raskt og enkelt skrive ut måleresultater. De kan også lagres i instrumentet for senere bruk.

Type tested Production monitored
Baumuster geprüft Produktion überwacht
TÜV SÜD
EN 50379

Nyhet

4 års garanti på insturment og probe

NYHET!

O_2

NO

°C

hPa

CO/H_2

ΔP

VVPARTS®
Tlf: 69 26 46 5[illegible] Fax: 69 26 46 99



Tekniske data		
Temperature	Meas. range	-40 to +1200 °C
	Accuracy	±0,5 °C (0.0 to +100.0 °C) ±0,5 % of mv (remaining range)
	Resolution	0.1 °C (-40 to 999,9 °C) 1 °C (remaining range)
Draught measurement	Meas. range	-9.99 to +40 hPa
	Accuracy	±0.02 hPa or ±5 % of mv (-0.50 to +0.60 hPa) ±0.03 hPa (+0.61 to +3.00 hPa) ±1.5 % of mv (+3.01 to +40.00 hPa)
	Resolution	0.01 hPa
Pressure measurement	Meas. range	0 to 200 hPa
	Accuracy	±0.5 hPa (0.0 to 50.0 hPa) ±1 % of mv (50.1 to 100.0 hPa) ±1.5 % of mv (remaining range)
	Resolution	0.1 hPa
O_2 measurement	Meas. range	0 to 21 Vol. %
	Resolution	0.1 Vol. %
	Accuracy	±0.2 Vol. %
	Adjustment time t_{90}	< 20 s
CO measurement (H2 compensated)	Meas. range	0 to 8000 ppm
	Resolution	1 ppm
	Accuracy	±10 ppm or ±10% of mv (0 to 200 ppm) ±20 ppm or ±5% of mv (201 to 2000 ppm) ±10% of mv (2001 to 8000 ppm)
	Adjustment time t_{90}	< 40 s
from 8000 ppm	Display range	8000 to 30000 ppm (automatic dilution)
	Resolution	500 ppm
Efficiency (Eta)	Meas. range	0 to 120 %
	Resolution	0.1 %
Flue gas loss	Meas. range	0 to 99.9 %
	Resolution	0.1 %
CO2 measurement	Display range	0 to CO2 max
	Resolution	0.1 Vol. %
	Accuracy	±0.2 Vol. %
	Determination	Digital calculation from O2
	Adjustment time t_{90}	< 40 s
Option: NO_{low} measurement	Meas. range	0 to 300 ppm
	Resolution	0.1 ppm
	Accuracy	±2 ppm (0.0 to 40.0 ppm) ±5% of mv (remaining range)
	Adjustment time t_{90}	< 30 s
Option: NO measurement	Meas. range	0 to 3000 ppm
	Resolution	1 ppm
	Accuracy	±5 ppm (0 to 100 ppm) ±5% of mv (101 to 2000 ppm) ±10% of mv (2001 to 3000 ppm)
	Adjustment time t_{90}	< 30 s
Ambient CO measurement (with CO probe)	Meas. range	0 to 500 ppm
	Resolution	1 ppm
	Accuracy	±5 ppm (0 to 100 ppm) ±5% of mv (>100 ppm)
	Adjustment time t_{90}	Approx. 35 s
Gas leak measurement for combustible gases (with gas leak detection probe)	Display range	0 to 10,000 ppm CH_4 / C_3H_8
	Signal	Optical display (LED) audible display via buzzer
	Adjustment time t90	< 2 s
Ambient CO_2 measurement (with ambient CO_2 probe)	Meas. range	0 to 1 Vol. % 0 to 10000 ppm
	Accuracy	±(50 ppm ±2 % of mv) (0 to 5000 ppm)
	Adjustment time t_{90}	Approx. 35 s
General Technical Data	Memory	200 Sites
	Weight	600 g (without rechargeable battery)
	Dimensions	270 x 90 x 65 mm
	Storage temp.	-20 to +50 °C
	Oper. temp.	-5 to +45 °C
	Display	Graphics display: 160 x 240 pixel
	Power supply	Rech. block: 3.7V/2.2Ah Power: 6V/1.2A
Warranty	testo 330-2 LL	Instrument/probe/cells (O_2, CO) 48 months NO, NO_{low} cell 24 months Thermocouple and rechargeable battery 12 months

Informasjon:

- Instrumentet inkluderer alle basisfunksjoner som forbrenningsvirkningsgrad, røykgasstap, O_2, CO_2, CO og trekk
- Robust og beskyttet mot støt/slag med deksel av elastisk plast
- Lett og bruke
- Effektiv å bruke takkevære raske menyer og snartveier på display
- Stort utvalg av prober kan ettermonteres
- Lav vekt 600g (standard batteri)
- 200 lagringsplasser i minnet
- USB interface for PC
- Kan koble på reletester, se side: 130.

Produkt:	Varenr:	Kode:	Pris:
Testo 330-2LL Røkgassanalysator Inneholder: Koffert, instrument, slangesett 300mm/2.2m, lader, 10 stk filter Måler: forbrenningsvirkningsgrad, røykgasstap, O2, CO2, CO og trekk, temperatur	0632 3305		
NO celle 0-3000 ppm *(ekstrautstyr - ved nyinstallasjon)*	0440 3922		
NO celle 0-300 ppm *(ekstrautstyr - ved nyinstallasjon)*	0440 3931		
Trådløs IR Printer *(inkl. en rull papir + 4 AA batterier)*	0554 0547		
Papir til printer *(6 ruller i en pakke)*	0554 0568		
Filter til slangesett *(10 stk i en pakke)*	0554 0040		
EasyHeat PC program *(fullversjon)*	0554 3332		
Slangesett 300mm 500°C *(2.2 meter lengde)*	0600 9761		

VVPARTS®
Tlf: 69 26 46 50 Fax: 69 26 46 99